



### 50M ABS SPECIFICATIONS

<b>Length Overall:</b>	164'-0" (50.0 M)
<b>Length at Waterline:</b>	149' 6.9" (43.7M)
<b>Beam Overall:</b>	29'6" (9.0M)
<b>Draft (Full) Est:</b>	8'0"
<b>Draft (Light) Est:</b>	7'6" (2.3M)
<b>US Tonnage:</b>	Less than 300 gross tons
<b>Displacement F/L:</b>	875.00 lbs
<b>Builder:</b>	Christensen Shipyards, LLC
<b>Interior Design:</b>	Christensen Shipyards, LLC
<b>Construction:</b>	Hull and Superstructure Vacuum Infused Composite
<b>Classification:</b>	ABS
<b>Main Engines:</b>	(2) MTU 12V 4,000 18751 HP
<b>Propulsion Shafting:</b>	(2) 5' Dia. 'Aqualoy-22"
<b>Electrical:</b>	(2) 99KW-208V-3PH-60Hz and (2) 76KW-208V-3PH-60Hz
<b>Max Speed:</b>	16 Knots
<b>Cruising Speed:</b>	12 Knots
<b>Fuel:</b>	15,300 US Gallons (57.916 Liters)
<b>Water:</b>	3,600 USG (13.627 Liters)
<b>Range:</b>	Over 4,000 Nautical Miles
<b>Owner/Guest:</b>	12 Guests in 6 Staterooms
<b>Crew:</b>	10 Crew in 5 Cabins